

AD-A089 391

AERONAUTICAL RESEARCH LABS MELBOURNE (AUSTRALIA)

F/6 11/4

A CRACK OPENING DISPLACEMENT APPROACH TO CRACK PATCHING, (U)

OCT 79 R JONES, R J CALLINAN

UNCLASSIFIED

ARL/STRUC NOTE-455

NL

1 OF 1  
88-0000

END

DATE

FILED

10-10

DTIC

**LEVEL**

12



AD A089391

**DEPARTMENT OF DEFENCE  
DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION  
AERONAUTICAL RESEARCH LABORATORIES**

MELBOURNE, VICTORIA

STRUCTURES NOTE 455

**A CRACK OPENING DISPLACEMENT APPROACH  
TO CRACK PATCHING**

by

R. JONES and R. J. CALLINAN

DTIC  
ELECTE  
SEP 15 1980

Approved for Public Release



UNITED STATES NATIONAL  
DEFENCE INFORMATION SERVICE  
IS NOTIFIED TO  
REPRODUCE AND SELL THIS REPORT

© COMMONWEALTH OF AUSTRALIA 1979

OCTOBER 1979

80 9 11 049

FILE COPY

COPY No 20

DEPARTMENT OF DEFENCE  
DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION  
AERONAUTICAL RESEARCH LABORATORIES

STRUCTURE NOTE 455

**A CRACK OPENING DISPLACEMENT APPROACH  
TO CRACK PATCHING**

by

R. JONES and R. J. CALLINAN

**SUMMARY**

*The results of a numerical investigation into crack patching indicate that a modified form of the crack opening displacement approach may be useful in estimating the effect that fibre composite patches have on cracks in thin sheets.*

POSTAL ADDRESS: Chief Superintendent, Aeronautical Research Laboratories,  
Box 4331, P.O., Melbourne, Victoria, 3001, Australia.

## DOCUMENT CONTROL DATA SHEET

**Security classification of this page: Unclassified**

- |  |   |
|--|---|
| <p><b>1. Document Numbers</b></p> <p>(a) AR Number:<br/>AR-001-768</p> <p>(b) Document Series and Number:<br/>Structures Note 455</p> <p>(c) Report Number:<br/>ARL-Struc-Note-455</p> | <p><b>2. Security Classification</b></p> <p>(a) Complete document:<br/>Unclassified</p> <p>(b) Title in isolation:<br/>Unclassified</p> <p>(c) Summary in isolation:<br/>Unclassified</p> |
|--|---|

### 3. Title: A CRACK OPENING DISPLACEMENT APPROACH TO CRACK PATCHING

4. **Personal Author(s):**  
Jones, R.  
Callinan, R. J.
5. **Document Date:**  
October, 1979
- 
6. **Type of Report and Period Covered:**

- |  |  |
|--|--|
| <p>7. Corporate Author(s):<br/>Aeronautical Research Laboratories</p> <hr/> <p>9. Cost Code:<br/>21 4670</p> | <p>8. Reference Numbers</p> <p>(a) Task:<br/>AIR 72/20</p> <p>(b) Sponsoring Agency:<br/>Dept. of Defence<br/>(Air Force Office)</p> |
|--|--|

- |   |   |
|---|---|
| <p><b>10. Imprint</b><br/> <b>Aeronautical Research Laboratories,</b><br/> <b>Melbourne</b></p> | <p><b>11. Computer Program(s)</b><br/> <b>(Title(s) and language(s)):</b></p> |
|---|---|

**12. Release Limitations (of the document):** Approved for public release

12-0. Overseas:	N.O.		P.R.	1	A		B		C		D		E
-----------------	------	--	------	---	---	--	---	--	---	--	---	--	---

- 13. Announcement Limitations (of the information on this page):**  
No limitations

- |                         |                    |                          |
|-------------------------|--------------------|--------------------------|
| <b>14. Descriptors:</b> |                    | <b>15. Cosati Codes:</b> |
| Cracking (fracturing)   | Metal sheets       | 1113                     |
| Fatigue (materials)     | Cracks             | 1104                     |
| Fiber composites        | Numerical analysis |                          |
| Maintenance             |                    |                          |

- 16.
- ABSTRACT*

*The results of a numerical investigation into crack patching indicate that a modified form of the crack opening displacement approach may be useful in estimating the effect that fibre composite patches have on cracks in thin sheets.*

Accession For	<input checked="checked" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
NIN. GRAFI	
Doc TAB	
Unannounced	
Classification	
For	
Dist. Location/	
Agency/Community Codes	
Dist	
Special	

## **CONTENTS**

	<b>Page No.</b>
<b>NOTATION</b>	
<b>1. INTRODUCTION</b>	<b>1</b>
<b>2. CORRELATION</b>	<b>1</b>
<b>3. PATCH EFFICIENCY MEASUREMENT TECHNIQUES</b>	<b>6</b>
<b>4. CONCLUSION</b>	<b>8</b>
<b>DISTRIBUTION</b>	

## NOTATION

$\sigma$	Applied tensile stress.
$G_{12}, G_{13}, G_{23}$	Shear moduli of the patch.
$E_1, E_2$	Young's moduli of the patch.
$\gamma_{12}$	Poissons ratio of the patch.
$t_a$	Thickness of adhesive layer.
$t_s$	Thickness of sheet.
$t_0$	Thickness of the patch.
$K_{1p}$	Stress intensity factor for the patched crack.
$K_{1u}$	Stress intensity factor for the unpatched crack.
$a$	Crack half length.
$\alpha$	Characteristic length.
$v_p$	Opening of the patched crack.
$v_u$	Opening of the unpatched crack.
$\epsilon_{py}$	Strain in the patch in the $y$ direction.
$v_{pa}$	Displacement in the patch in the $y$ direction.

## 1. INTRODUCTION

This paper forms part of a detailed investigation into the repair of aircraft structural components, using bonded composite overlays, currently underway at the Aeronautical Research Laboratories, Australia [1-6]. To date a large number of cracked components have been successfully repaired in this fashion; these include wing skins, wing planks, and wheels (see Ref. [2]). The present paper is concerned with an observed correlation between the reduction of the opening of a patched crack, at any point along the crack, and the reduction in the stress intensity factor due to patching. This correlation raises the possibility of using crack opening displacement measurements as a measure of patch efficiency.

## 2. CORRELATION

Let us begin by considering a thin rectangular sheet of dimensions  $508 \text{ mm} \times 635 \text{ mm} \times t_s \text{ mm}$ , where the thickness  $t_s$  will be allowed to vary, subjected to a uniform tensile stress  $\sigma$ . The sheet contains a central crack  $38.1 \text{ mm}$  long which is patched by a boron epoxy laminate covering the entire length of the crack. The laminate is uniaxial, the fibres lying perpendicular to the length of the crack. The lateral dimensions of the patch are  $152.4 \text{ mm} \times 50.8 \text{ mm} \times t_p$  where  $t_p$  is the thickness of the patch and will be allowed to vary (see Fig. 1).

The patch is bonded to the sheet with an epoxy resin of thickness  $t_a$ . The Young's modulus of the sheet is  $71.02 \text{ GPa}$  while the Poisson's ratio is  $0.32$ . The moduli of the laminate are

$$\begin{aligned} E_1 &= 208.1 \text{ GPa} & G_{12} &= G_{13} = 7.24 \text{ GPa} \\ E_1/E_2 &= 8.18 & G_{23} &= 4.94 \text{ GPa} \\ \gamma_{12} &= 0.1677 \end{aligned}$$

where the 1-axis is in the fibre direction;  
the 2-axis is parallel to the crack;  
the 3-axis is in the thickness direction.

This problem was analysed using the finite element method and uses the advanced crack tip element developed by the authors in [3] and the adhesive element, which allows for transverse shear deformation in the sheet and the patch, described in [4]. Various types of patches were considered including constant thickness patches applied to one or both sides of the sheet and stepped thickness patches (see Fig. 2).

1. A. A. Baker.—Evaluation of adhesives for fibre composite reinforcement of fatigue cracked aluminium. Proc. 10th Nat. SAMPE Technical Conference pp. 397-415, (1978).
2. A. A. Baker.—A Summary of Work on Applications of Advanced Fibre Composites at the Aeronautical Research Laboratories, Australia, Composites, Vol. 9, pp. 11-16, (1978).
3. R. Jones and R. J. Callinan.—On the use of Special Crack Tip Elements in Cracked Elastic Sheets, Int. J. Fracture, Vol. 13, 1, pp. 51-64, (1977).
4. R. Jones and R. J. Callinan.—Finite Element Analysis of Patched Cracks, J. Structural Mechanics, Vol. 7, 2, pp. 107-129, 1979; also published as ARL Structures Report 367, 1978.
5. M. J. Davis.—Stress Intensity Reduction by Strategic Reinforcement, Proc. 1977 Conference Australian Fracture Group, pp. 90-101, (1977).
6. R. Jones and R. J. Callinan.—Developments in the Analysis and Repair of cracked and uncracked Structures. Proceedings 3rd International Conference on Finite Element Methods in Engineering, Sydney July 1979, pp. 231-245, (1979).




FIG 1 PATCHED TENSION PANEL (dimensions in mm)






FIG 2 PATCH GEOMETRY



(a) Crack opening displacement



(b) Points of evaluation of the patch efficiency

FIG 3.

The point of interest in the present investigation is the correlation between the calculated values of the stress intensity factor for a patched crack and the opening up of the crack at various points along its length. This correlation is studied by evaluating on the one hand the non-dimensionalized reduction in the stress intensity factor given by,

$$1 - K_{1p}/K_{1u}$$

where  $K_{1p}$  is the stress intensity factor for the patched crack and  $K_{1u}$  is the stress intensity factor for the unpatched crack. On the other hand we also evaluate, at various points along the crack, a quantity which we term the "patch efficiency" and which we define by

$$\text{patch efficiency} = 1 - v_p/v_u \quad (1)$$

where  $v_p$  is the displacement of a point on the patched crack and  $v_u$  is the displacement of the corresponding point on the unpatched crack. These displacements are in the direction perpendicular to the length of the crack i.e., the crack opening displacements. With this notation the unpatched crack yields a patch efficiency of zero, whilst a patch efficiency of unity occurs when the patched crack does not open up during loading.

In all cases studied the patch efficiency was evaluated at the five points along the crack shown in Figure 3b. The coordinates of points 1-5 are (0, 0), ( $a/3$ , 0), ( $2a/3$ , 0), ( $0.76a$ , 0), ( $0.86a$ , 0) respectively where  $a$  is the half crack length. It should be mentioned that it is a well established result in linear elastic fracture mechanics that the crack opening displacement, in the case of unpatched cracks, very close to a crack tip (such as point 5) is directly proportional to the stress intensity factor.

In Table 1 we see the effect that increasing the thickness of the patch has upon both the calculated values of the patch efficiency and the reduction in the stress intensity factor; these results are all for constant thickness patches.

**TABLE 1**  
**Correlation for Constant Thickness Patches**  
( $t_a = 0.1016$  mm,  $t_s = 2.29$  mm)

Patch Thickness (mm) on one side only	Patch efficiency at points:					$1 - K_{1p}/K_{1u}$
	1	2	3	4	5	
<b>Reinforced on each side of the sheet</b>						
0.762	0.90	0.88	0.88	0.88	0.88	0.88
0.508	0.88	0.86	0.86	0.86	0.87	0.87
0.381	0.86	0.85	0.84	0.85	0.86	0.86
0.254	0.84	0.82	0.81	0.82	0.85	0.85
0.127	0.78	0.76	0.76	0.77	0.79	0.79
<b>Reinforced on one side only</b>						
1.016 mm	0.81	0.80	0.79	0.79	0.81	0.81
0.762	0.79	0.78	0.77	0.77	0.79	0.79
0.508	0.77	0.75	0.74	0.74	0.76	0.76
0.254	0.71	0.69	0.68	0.69	0.73	0.73
0.127	0.63	0.61	0.61	0.62	0.66	0.66

Here we see that, to a reasonable approximation the patch efficiency is constant along the entire length of the crack. This constant value agrees closely with the reduction in the stress intensity factor due to patching.

Whereas in Table 1 the thickness of the sheet was held constant at  $t_s = 2.29$  mm and the patch thickness was varied, in Table 2 the thickness of the sheet was allowed to vary. Here

the patch is the step thickness patch shown in Figure 2(c) which is of the same plan form as the previous patches; this patch comprises six layers of boron on each side of the sheet.

**TABLE 2**  
**Correlation for Step Thickness Patches**  
( $t_a = 0.1016$  mm)

Sheet Thickness (mm)	Patch efficiency at points					$1 - K_{1p}/K_{1u}$
	1	2	3	4	5	
5.08	0.78	0.77	0.76	0.76	0.78	0.78
3.81	0.84	0.83	0.81	0.82	0.83	0.83
2.29	0.91	0.90	0.89	0.89	0.89	0.89
1.27	0.95	0.95	0.94	0.94	0.94	0.94
0.64	0.98	0.97	0.97	0.97	0.97	0.97

Again we see that the patch efficiency is virtually constant along the entire length of the crack and agrees closely with the reduction in stress intensity.

So far we have only considered an adhesive thickness of 0.1016 mm, which is commercially available; another thickness which is also available is 0.2032 mm. Table 3 shows the effect that this twofold increase in adhesive thickness has upon the patch efficiency for the stepped patch considered above and for a sheet thickness of 2.29 mm.

**TABLE 3**  
**Further Correlation for Step Thickness Patches**  
( $t_s = 2.29$  mm)

Patch efficiency at points					$1 - K_{1p}/K_{1u}$
1	2	3	4	5	
0.88	0.89	0.88	0.88	0.88	0.88

Yet again we see that the patch efficiency is effectively constant along the entire crack length, and coincides with the reduction in the stress intensity factor.

We thus see that, in this limited study, the patch efficiency is a good estimate of the reduction in the stress field at the tip of a crack. Furthermore, computing the patch efficiency at the centre of the crack, or at a point removed from the tip, removes the necessity of having special crack tip elements and yet still allows an estimate to be made of the reduction in the stress intensity factor due to patching.

### 3. PATCH EFFICIENCY MEASUREMENT TECHNIQUES

The concept of patch efficiency may also be a useful experimental tool since the opening of the crack may easily be measured when the crack is unpatched and may be derived as follows, from strain gauge measurements on the patch when the crack is patched.

Let us consider a panel with a centrally located crack, of length  $2a$ . Define a system of  $x, y$  coordinates with origin at the centre of the crack and with the  $y$  axis perpendicular to the crack. Then in the case of mode I fracture the displacement, in the  $y$  direction, at any point  $(x, \alpha)$  in the patch is given by




FIG 4(a). VARIATION OF FIBRE STRESS ALONG PATCH CENTER LINE




FIG 4(b). VARIATION OF SHEAR STRESS ALONG PATCH CENTER LINE

$$v_{pa}(x, \alpha) = \int_0^{\alpha} \epsilon_{py} dy \quad (2)$$

where  $\epsilon_{py}$  is the strain in the patch in the  $y$  direction. The effect that the crack has upon the strain  $\epsilon_{py}$  in the patch is discussed in detail in Reference [7] and is shown in Figure 4 for the full thickness patch, of Figure 2(a), which has  $t_a = 0.1016$  mm,  $t_s = 2.29$  mm and  $t_p = 0.762$  mm. From these references and from Figure 4 we see that we can choose a value for  $\alpha$ , which is less than the crack length, such that at  $y = \alpha$  the shear stress in the adhesive and the derivative of the extensional strain in the patch i.e.  $d\epsilon_{py}/dy$  are both effectively zero.

Since, at this point, the shear stress is zero the movement, in the  $y$  direction, in the sheet, which we will denote by  $v_s(x, \alpha)$ , is exactly equal to the movement in the patch, i.e.

$$\begin{aligned} v_s(x, \alpha) &= v_{pa}(x, \alpha) \\ &= \int_0^{\alpha} \epsilon_{py} dy \end{aligned} \quad (3)$$

Expanding  $v_s(x, \alpha)$  by means of Taylor's theorem we see that

$$v_s(x, 0) = v_s(x, \alpha) - \alpha \left( \frac{\partial v_s}{\partial y} \right)_{y=\alpha} + o(\alpha^2) \quad (4)$$

However we have chosen  $\alpha$  such that at  $y = \alpha$   $v_s = v_{pa}$  and as a result

$$\begin{aligned} \left( \frac{\partial v_s}{\partial y} \right)_{y=\alpha} &= \left( \frac{\partial v_{pa}}{\partial y} \right)_{y=\alpha} \\ &= \epsilon_{py}(x, \alpha) \end{aligned} \quad (5)$$

(i.e. strain in the patch = strain in the sheet)

Consequently substituting for  $\partial v_s / \partial y$ , as given by equation (5), into equation (4) and rearranging terms we see that

$$v_s(x, 0) = v_s(x, \alpha) - \alpha \epsilon_{py}(x, \alpha) \quad (6)$$

where the terms of order  $\alpha^2$  and higher have been omitted since at  $x = \alpha$  the derivatives of  $\epsilon_{py}$  with respect to  $y$  are zero.

Recalling that  $v_s(x, \alpha) = \int_0^{\alpha} \epsilon_{py} dy$  we finally obtain the relationship

$$v_s(x, 0) = \int_0^{\alpha} \epsilon_{py}(x, \alpha) dy - \alpha \epsilon_{py}(x, \alpha) \quad (7)$$

Since  $v_s(x, 0)$  is the opening of the crack we see that the opening of the crack at any point  $x$  along its length may be directly calculated once the strain in the patch is known.

As can be seen from Reference [4] (Figs 5, 6, 7 and 8) as  $x$  approaches the value of  $a$ , i.e. near the crack tip, the value of  $\alpha$  necessary to satisfy the requirements of zero shear stress etc. reduces significantly. For example whereas from Figure 4, where  $x = 0$ , the minimum allowable value of  $\alpha$  is approximately  $\alpha = a$  (the half crack length) from Figure 8 of Reference [4], for the case  $x = a$ , the minimum allowable value is approximately  $a/3$ .

#### 4. CONCLUSION

A limited numerical study has shown that there is a very good correlation between the patch efficiency and the reduction in the stress intensity factor due to patching. We have also

7. R. Jones and R. J. Callinan.—A Design Study in Crack Patching. A.R.L. Structures Report 376, 1979.

seen that the patch efficiency can be obtained from a knowledge of the crack opening displacements of the unpatched crack and from strain gauge measurements on the patch. This approach may have some advantages over the present method for experimentally estimating the reduction in the stress intensity factor which is based on the increase in fatigue life due to patching. Indeed, since this reduction is often dramatic, the fatigue life is generally increased by at least an order of magnitude and quite often no crack growth is recorded.

## DISTRIBUTION

Copy No.

### AUSTRALIA

#### Department of Defence

##### Central Office

Chief Defence Scientist	1
Deputy Chief Defence Scientist	2
Superintendent, Science and Technology Programs	3
Australian Defence Scientific and Technical Representative (U.K.)	4
Counsellor, Defence Science (U.S.A.)	5
Joint Intelligence Organisation	6
Defence Library	7
Document Exchange Centre, D.I.S.B.	8-23

##### Aeronautical Research Laboratories

Chief Superintendent	24
Library	25
Superintendent — Structures Division	26
Divisional File — Structures	27
Authors: R. Jones	28
R. J. Callinan	29
B. C. Hoskin	30

##### Materials Research Laboratories

Library	31
---------	----

##### Defence Research Centre, Salisbury

Library	32
---------	----

##### Central Studies Establishment

Information Centre	33
--------------------	----

##### Engineering Development Establishment

Library	34
---------	----

##### RAN Research Laboratory

Library	35
---------	----

##### Defence Regional Office

Library	36
---------	----

##### Navy Office

Naval Scientific Adviser	37
--------------------------	----

##### Army Office

Army Scientific Adviser	38
Royal Military College Library	39
US Army Standardisation Group	40

##### Air Force Office

Aircraft Research & Development Unit, Scientific Flight Group	41
Air Force Scientific Adviser	42
Technical Division, Library	43

D. Air Eng.-AF	44	
HQ Support Command (SENGSO)	45	
RAAF Academy, Point Cook	46	
<b>Department of Productivity</b>		
<b>Government Aircraft Factories</b>		
Manager/Library	47	
<b>Department of Transport</b>		
Secretary	48	
Library	49	
Airworthiness Group, Mr. K. O'Brien	50	
<b>Statutory, State Authorities and Industry</b>		
CSIRO, Mechanical Engineering Division, Chief	51	
CSIRO, Materials Science Division, Director	52	
Qantas, Library	53	
Trans Australia Airlines, Library	54	
Ansett Airlines of Australia, Library	55	
BHP, Central Research Laboratories, NSW	56	
BHP, Melbourne Research Laboratories	57	
Commonwealth Aircraft Corporation:		
Manager	58	
Manager of Engineering	59	
Hawker de Havilland Pty. Ltd.:		
Librarian, Bankstown	60	
Manager, Lidcombe	61	
<b>Universities and Colleges</b>		
Adelaide	Barr Smith Library	62
	Professor of Mechanical Engineering	63
Flinders	Library	64
James Cook	Library	65
Latrobe	Library	66
Melbourne	Engineering Library	67
Monash	Library	68
	Professor I. J. Polmear	69
Newcastle	Library	70
New England	Library	71
Sydney	Engineering Library	72
	Professor G. A. Bird	73
N.S.W.	Physical Sciences Library	74
Queensland	Library	75
Tasmania	Engineering Library	76
West. Australia	Library	77
R.M.I.T.	Library	78
<b>CANADA</b>		
Aluminium Laboratories Ltd., Library		79
CAARC Coordinator Structures		80
International Civil Aviation Organization, Library		81
Physics and Metallurgy Research Laboratories, Dr. A. Williams		82
NRC, National Aeronautical Establishment, Library		83
NRC, Division of Mechanical Engineering, Director		84
<b>Universities and Colleges</b>		
McGill	Library	85
Toronto	Institute for Aerospace Studies	86

<b>FRANCE</b>		
AGARD, Library		87
ONERA, Library		88
Service de Documentation, Technique de l'Aeronautique		89
<b>GERMANY</b>		
ZLDI		90
<b>INDIA</b>		
CAARC Co-ordinator Materials		91
CAARC Co-ordinator Structures		92
Civil Aviation Department, Director		93
Defence Ministry, Aero Development Establishment, Library		94
Hindustan Aeronautics Ltd., Library		95
Indian Institute of Science, Library		96
Indian Institute of Technology, Library		97
National Aeronautical Laboratory, Director		98
<b>ISRAEL</b>		
Technion— Israel Institute of Technology, Professor J. Singer		99
<b>ITALY</b>		
Associazione Italiana di Aeronautica e Astronautica		100
<b>JAPAN</b>		
National Aerospace Laboratory, Library		101
<b>Universities</b>		
Tohoku (Sendai) Library		102
Tokyo Inst. of Space and Aeroscience		103
<b>NETHERLANDS</b>		
Central Org. for Applied Science Research TNO, Library		104
National Aerospace Laboratory (NLR), Library		105
<b>NEW ZEALAND</b>		
Defence Scientific Establishment, Librarian		106
Transport Ministry, Civil Aviation Division, Library		107
<b>Universities</b>		
Canterbury Library		108
<b>SWEDEN</b>		
Aeronautical Research Institute		109
Chalmers Institute of Technology, Library		110
Kungliga Tekniska Hogskolan		111
SAAB-Scania, Library		112
Research Institute of the Swedish National Defence		113
<b>UNITED KINGDOM</b>		
Mr. A. R. G. Brown, ADR/MAT (MEA)		114
Aeronautical Research Council, Secretary		115
CAARC, Secretary		116
Royal Aircraft Establishment:		
Farnborough, Library		117
Bedford, Library		118
Commonwealth Air Transport Council Secretariat		119
Aircraft and Armament Experimental Establishment		120

Admiralty Materials Laboratories, Dr. R. G. Watson	121
National Engineering Laboratories, Superintendent	122
British Library, Science Reference Library	123
British Library, Lending Division	124
Naval Construction Research Establishment, Superintendent	125
CAARC Co-ordinator, Structures	126
Aircraft Research Association, Library	127
British Non-Ferrous Metals Res. Assoc.	128
British Ship Research Association	129
Rolls-Royce (1971) Ltd.:	
Aeronautics Division, Chief Librarian	130
Bristol Siddeley Division T.R. & I. Library Services	131
Science Museum Library	132
Welding Institute, Library	133
British Aerospace Corporation:	
Brough, Library	134
Greensgate, Library	135
Kingston-upon-Thames, Library	136
Hatfield Library	137
British Aircraft Corporation (Holdings) Ltd.:	
Commercial Aircraft Division	138
Military Aircraft Division	139
British Hovercraft Corporation Ltd., Library	140
Short Brothers Harland	141
Westland Helicopters Ltd.	142

#### Universities and Colleges

Bristol	Library, Engineering Department	143
Cambridge	Library, Engineering Department	144
Belfast	Dr. A. Q. Chapleo, Dept. of Aeron. Engineering	145
Manchester	Professor, Applied Mathematics	146
Nottingham	Library	147
Southampton	Library	148
Strathclyde	Library	149
Cranfield Inst. of Technology	Library	150
Imperial College	The Head	151

#### UNITED STATES OF AMERICA

NASA, Scientific and Technical Information Facility	152
Sandia Group Research Organisation	153
American Institute of Aeronautics and Astronautics	154
Applied Mechanics Review	155
The John Crerar Library	156
The Chemical Abstracts Service	157
Bell Helicopter Textron	158
Boeing Commercial Airplane Co.:	
Head Office, Mr. R. Watson	159
Industrial Production Division	160
Cessna Aircraft Co., Executive Engineer	161
Lockheed Missiles and Space Company	162
Lockheed California Company	163
Lockheed Georgia Company	164
McDonnell Douglas Corporation, Director	165
Metals Abstracts, Editor	166
Calspan Corporation (Formerly Cornell Aero Labs.)	167

United Technologies Corporation:	
Pratt and Whitney Aircraft Group	168
Battelle Memorial Institute, Library	169

#### Universities and Colleges

Florida	Aero. Engineering Dept.	170
Stanford	Department of Aeronautics Library	171
Brooklyn Inst. of Polytech.	Polytech. Aeronautical Labs. Library	172
California Inst. of Technology	Guggenheim Aeronautical Labs. Library	173
Massachusetts Inst. of Technology	Library	174

Spares	175-184
--------	---------